

SLS Series

Model: SLS-CA

Submersible level sensor

- Ceramic sensor, analogue



Description:

The SLS-CA series of submersible level transmitters have been developed using a ceramic diaphragm piezo-resistive sensing element housed in a robust stainless steel housing. It has a proprietary cable gland assembly to provide permanent submersible in liquids up to 100m depth for continuous operation.

The device is available in either a raw millivolt output which is great for low power applications or an internal microprocessor is fitted to provide an amplified output such as 4-20mA, 0-10V, 0.5 to 4.5V ratiometric.


The onboard 16-bit microprocessor enables a high level of linearisation, temperature compensation and calibration to be performed ensuring the highest accuracy, stability and repeatability are met for demanding applications such as environmental monitoring and flood defence systems, river, reservoir or borehole measurement.

Product Highlights:

- Level ranges from 5mWG up to 100mWG
- Accuracy $<\pm 0.25\%$, $<\pm 0.15\%$
- 316 St/St or Marine Bronze CA104
- High integrity cable gland assembly
- Various output configurations available
- Low power consumption millivolt signal
- Temperature output, optional

Applications include, but not limited to:


- Environmental monitoring
- V-notch weir flow measurement
- Rivers, reservoirs and boreholes
- Tank, IBC, Tote level measurement
- Telemetry and data logging
- Flood defence monitoring and research
- Academic research



STORKSOLUTIONS

Specification:


Submersible Level Sensor, Digital - SLS-CA	
Sensor technology	Piezo-resistive Ceramic Sensor
Output Versions	4-20mA (2-wire), 0-5V/0-10V (3-wire), 0.5 to 4.5V (3-wire ratiometric)
Supply voltage	4-20mA: 8 - 32V dc / 0-5V/0-10V/: 12 - 32V dc / Ratiometric: 2.7 - 5.5V dc
Response time	<10ms
Pressure reference	Gauge (standard), Sealed Gauge, Absolute
Level ranges	5, 10, 20, 30, 50, 100mWG
Safe over pressure	1.5 times rated pressure
Burst Pressure	3 times rated pressure
Accuracy (NL&H)	$\leq \pm 0.25\%$ / $\leq \pm 0.15\%$
Long term stability:	$\leq \pm 0.10\%$ FS
Compensated temperature range	20 °C $\pm$ +20 °C
Media temperature	-10 °C to +60 °C, non-freezing
Temperature effects	Typical thermal zero and span coefficients $\pm 0.015\%$ FS/ °C
Supply reverse polarity protection	No damage but also no function
Lightning Protection	Integral GDS (gas discharge tube) for lightning protection
Electromagnetic compatibility	CE Compliant
Media wetted parts	Sensor: Ceramic Al ₂ O ₃ , Housing: 316 ST/ST or Marine Bronze CA104, Seals: FKM, EPDM or NBR, Cable: PUR
Permissible media	All fluids compatible with media wetted parts
Electrical connection	PUR submersible cable, terminated in tails. Internal vent tube
Pressure connection	Nose cone, G1/4" DIN 3852 male when unscrewed
Current consumption	4-20mA: dependant on output signal / 0-5V/0-10V/: 6mA / Ratiometric: 2.5mA
Weight (g)	Transmitter: <270g, Cable: 48g per mtr
Environmental Protection	IP68, Fully submersible up to 100m depth




STORK SOLUTIONS

Dimensional Drawings:

SLS Series - Submersible level sensor - SLS-CA






STORK SOLUTIONS

Part Numbering system

SLS-CA - Submersible Level Transmitter, ceramic sensor, analogue SLS-CA - X X - X X X X - X X - X X X X X X X X														
Output Type														
mV/V	A													
4-20mA (2-wire)	D													
0-5V (3-wire)	E													
1-5V (3-wire)	F													
0-10V (3-wire)	G													
0.5 to 4.5V (3-wire)	H													
Accuracy Class														
0.25%	B													
0.15%	C													
Cable Material														
PUR	A													
Cable Length (m)														
2		0	0	2										
3		0	0	3										
5		0	0	5										
10		0	1	0										
15		0	1	5										
20		0	2	0										
25		0	2	5										
30		0	3	0										
40		0	4	0										
50		0	5	0										
100		1	0	0										
Special Length... On request		9	9	9										
Housing Material														
316 Stainless Steel								A						
Marine Bronze CA104								M						
Seal Material														
FKM								V						
(Drinking Water Approved) EPDM								E						
NBR								N						
Range														
0 - 5mWG									0	5	0	0		
0 - 10mWG									1	0	0	0		
0 - 20mWG									2	0	0	0		
0 - 30mWG									3	0	0	0		
0 - 50mWG									5	0	0	0		
0 - 100mWG									1	0	0	1		
Special Range... On request									9	9	9	9		
Pressure Datum														
Gauge													G	
Sealed Gauge													S	
Absolute													A	
Special Options														
None													0	0




STORK SOLUTIONS

Accessories:

NPT Threaded Adaptor



Vented Junction Box



Cable Hanger

